



ÇALIŞMA BASINCI / OPERATING PRESSURE	16 BAR
MAX.TEST BASINCI / MAX.TEST PRESSURE	24 BAR
ÇALIŞMA ÜST SICAKLIĞI TOP WORKING TEMPERATURE	≤ 150 °C
UYGULAMA SIVISI / APPLICABLE MEDIUM	SU, YAĞ, BUHAR, vb./ WATER ,OIL ,STEAM etc.

NO:	PARÇA ADI / PART NAME	MALZEME / MATERIAL
1	ALT KAPAK / LOWER COVER	F316-A182
2	ÇİVATA / BOLT	B8M-A193
3	SIZDIRMAZLIK CONTASI / SEAL GASKET	GRAFİT/ GRAPHITE
4	ALT YATAKLAMA KAPLİNİ / DOWN BEARING BUSHING	KENDİNDEN YAĞLANAN RULMAN / SELF-LUBRICATING BEARING
5	GÖVDE / BODY	SS314 / SS316 / A351
6	ÇİVATA / BOLTS	B8M-A193
7	KELEPÇE / CLAMP	F316-A182
8	SIZDIRMAZLIK HALKASI / SEAL RING	RPTFE
9	DİSK / DISC	CF8M-A351
10	MİL / STEM	17-4PH
11	PİM / PIN	17-4PH
12	YATAKLAMA KAPLİNİ / BEARING BUSHING	F316-A182
13	ÜST YATAKLAMA KAPLİNİ / UP BEARING BUSHING	KENDİNDEN YAĞLANAN RULMAN / SELF-LUBRICATING BEARING
14	V PAKET / V TYPE PACKING	GRAFİT / GRAPHITE
15	BOĞAZ SALMASTRASI / PACKING GLAND	CF8M-A351
16	ÇİVATA / BOLT	B8M-A193
17	SOMUNLAR / NUTS	8M-A194
18	BRAKET / BRACKET	AISI 1020
19	ÇİVATA / BOLT	B7-A193
20	SOMUNLAR / NUTS	2H-A194
21	DİŞLİ KUTUSU / WORM GEAR	

ÖLÇÜ / SIZE	L	H	H1	D	D1	N-Ø	A	B	W	T.(N.M)	AĞIRLIK / WEIGHT (KGS)		
											KOLSUZ WITHOUT HANDLE	KOLLU WITH HANDLE	DİŞLİ KUTULU GEAR BOX
DN50	43	162	64	102	165	4-18	174	50	210	24			
DN65	46	172	70	122	165	4-18	174	50	210	35			
DN80	48	182	85	138	160	8-18	174	50	210	47			
DN100	54	206	92	157,2	180	8-18	174	50	210	75			
DN125	57	222	120	185,7	210	8-18	174	50	210	75			
DN150	57	314	150	216	240	8-22	260	63	300	260			
DN200	64	349	187	268	295	12-22	260	63	300	420			
DN250	71	377	220	324	355	12-26	317	80	380	558			
DN300	81	431	235	378	410	12-26	284	90	380	1200			
DN400	102	506	320	490	525	4-M27	330	139	480	2400			
DN500	127	561	372	610	650	4-M30	470	138	600	3800			